

Part Number: 1309A

Speaker Cable, 2 Conductor 14 AWG, BC, Unshielded, CM



Product Description

Speaker Cable, CL3 & CM-Rated, 2-14 AWG stranded high conductivity bare copper conductors with polyolefin insulation, PVC jacket with sequential footage marking every two feet

Technical Specifications

Product Overview

Environmental Space:	Indoor (Not Riser or Plenum)	
Suitable Applications:	Speaker Cable, Direct Burial, Indoor/Outdoor Home Theater, In-Wall Speaker, Outdoor Speaker	l

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material		Nominal Diameter	No. of Conductors
14	105x34	High Conductivity BC -	Bare Copper	0.074 in	2
Condu	ctor Count:		2		
Condu	Conductor Size:		14 AWG		

Insulation

Material	Nominal Diameter
PO - Polyolefin	0.105 in

Color Chart

Number	Color
1	Black
2	Red

Outer Shield Material



Outer Jacket Material

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.264 in

Electrical Characteristics

Conductor DCR



Capacitance

Nom. Capacitance Conductor to Conductor 20.5 pF/ft

Inductance

Nominal Inductance

Delay

Nominal Velocity of Propagation (VP) [%]

66 %

Current

Max. Recommended Current [A]

13 Amps per conductor @ 25°C

Voltage

UL Voltage Rating

300 V RMS

Temperature Range

UL Temp Rating:	75°C
Operating Temp Range:	-20°C To +75°C

Mechanical Characteristics

Bulk Cable Weight:	42 lbs/1000ft
Max Recommended Pulling Tension:	104 lbs
Min Bend Radius/Minor Axis:	2.75 in

Standards

NEC/(UL) Specification:	CL3, CM
CEC/C(UL) Specification:	CM
CPR Euroclass:	Eca

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU RoHS Compliance Date (yyyy-mm-dd):	2005-07-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Suitability

Suitability - Indoor:	Yes	
Suitability - Outdoor:	Yes	

Flammability, LS0H, Toxicity Testing

UL Flammability: UL1581 Vertice		UL1581 Vertical Flame and FT-1 Flame Test
	CSA Flammability:	FT1
	UL voltage rating:	300 V RMS

Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	6100UE

Part Number

Variants

Item #	Color	Footnote
1309A 0101000	Black	С
1309A 010U500	Black	
1309A 006U500	Blue, Light	
1309A 0081000	Gray	С
1309A 008U500	Gray	

Footnote:		C - CRATE REEL PUT-UP.		
1309A 1SLU500	White 1SL			
1309A 1SL1000	White 1SL	С		
1309A N3UU500	Green, Mil	С		

© 2019 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.