

CHORUS 716 V

Product specification sheet



6 1/2" (165mm) Polyglass midbass.
Highly dynamic medium.

6 1/2" (165mm) Polyglass woofer.
High power handling.

Front-firing port for bass impact.

Aluminum/Magnesium inverted dome TNV tweeter.
Extended response to 28kHz, ready for SACD.

Solid MDF construction up to 1" (25mm) width.
Non parallel inner wall structure.

OPC crossover.
Perfect staging.
New insulated Focal terminals.



- ◆ Speakers designed and manufactured by Focal.
- ◆ A sound quality never before seen at this price level.
- ◆ Amati finish.

Type	2 1/2-way bass-reflex floorstanding loudspeaker
Drivers	6 1/2" (165mm) Polyglass woofer 6 1/2" (165mm) Polyglass mid-bass 1" (25mm) TNV Al/Mg inverted dome tweeter
Frequency response (+/- 3dB)	50Hz-28kHz
Low frequency point (-6dB)	41Hz
Sensitivity (2.83V/1m)	91.5dB
Nom. impedance	8 ohms
Minimum impedance (@25°C)	4.3 ohms @ 146Hz
Max. power handling	200W
Power RMS	130W
Crossover frequency	300Hz / 3000Hz
Dimensions (HxWxD)	37 3/8 x 8 3/4 x 13 3/8" {950x222x340mm}
Net weight	45.1lbs {20.5kg}

The Chorus 716 V examines the 2-and-a-half way formula in a high-end configuration, with two 16.5 cm woofers working in tandem in the bass (only the higher unit also reproduces the midrange) Double the bass impact for rooms up to 30 m².

