



CL-70v-6UL
Commercial In-Ceiling



CL-70v-6UL

The CL-70v-6UL speaker is UL 1480 listed and meets the requirements of UL® 2043 for installation in air-handling spaces. It is engineered with wide dispersion, which is ideal for commercial applications such as restaurants, bars, stores, office buildings, hotels and classrooms. The CL-70 is designed with an industrial strength metal back can, which provides enhanced audio performance and component protection. The CL-70 also works with TruAudio's B-70 tile bridge for drop ceilings and is humidity rated for covered outdoor venues.

The finishing touch on this great speaker is our signature Ghost™-style grill!






LISTED
UL 1480




Frameless
Grill

CL-70v-6UL

Speaker Type:	2-way, in-ceiling, 70v
Woofers:	6.5" polypropylene
Tweeter:	.75" PEI
Power:	5 - 60 watts
Impedance:	8 Ω or 70V/100V
70v Taps:	2.5W - 25W selectable
100v Taps:	5W - 25W selectable
Freq Response:	55 - 20k Hz (+/-3 dB)
Sensitivity:	88 dB
Grill Type:	Ghost style, frameless
Colors Available:	White
Finish Dims:	10.4" (264mm) diameter, 9" (229mm) deep
Cutout Dims:	8.8" (224mm) diameter
UL Listing:	UL 1480
Family:	 UNIVERSAL

OPTIONAL ACCESSORY



B-70