



**Cable Station Hi-Definition  
CM or CL2, UV Resistant**

*Miniature Coaxial Cable*

*24 AWG 1C Stranded Oxy-Free Copper*

**Item # CXSCHED250**

Colors Offered - Red, Green, Blue, Black



Item Number UL Style	AWG (Strand) Size/Type Nom. D.C.R.	Dielectric Type Nom. Od	Shield Type Coverage Nom. D.C.R.	Jacket Type & Thickness	Cable Color & Jacket OD
<b>CXSCHD</b> <b>UV Resistant</b> <b>UL: CM OR CL2</b> <b>CSA: CM</b>	24 AWG 41/40 OFBC 28.1 Ω/M' 92.19 Ω/km	Gas Injected Foam PE .126"	AL Foil 95% TC Braid 1.5Ω/M' 4.9Ω/km	TPE .020"	Black .187" - .002" + .010"

Nom. Imp. (ohms)	Vel. Of Prop.	Nom. Cap. pF/ft. (pF/m)	Wt. Per Thousand Ft	Max. Pulling Tension	Max. Bending Radius
75Ω	75%	18.2 (59.7)	18 LBS	2359 PSI	2.25 Inches

**ATTENUATION SWEEP TESTED FROM 1MHZ To 3.0GHZ**

Frequency MHz	Nom. Atten. (dB/100ft)	Nom. Atten. (dB/100m)	Frequency MHz	Nom. Atten. (dB/100ft)	Nom. Atten. (dB/100m)
1	0.24	0.79	1000	8.46	27.75
3.6	0.46	1.51	1200	9.35	30.67
10	0.77	2.53	1450	10.39	34.07
71.5	2.10	6.89	1800	11.72	38.44
135	2.92	9.57	2000	12.44	40.80
270	4.19	13.74	2250	13.30	43.62
360	4.87	15.97	2400	13.80	45.26
720	7.07	23.19	3000	17.67	57.96

**Print: "[Logo] Planet Waves - CXSCHED - CableStation Hi-Definition 24AWG 75 Ω Coax Cable -**

**E116684 CM C(UL)US or (UL) CL2 UV-Resistant"**

\*Ascending & descending footage markers

