

D8TURBO

HD 1080p Turbo HD Indoor Dome Camera

epcom®



► Camera

Image Sensor	1/3" Progressive Scan CMOS
Signal System	PAL / NTSC
Effective Pixels	1920(H) * 1080(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR 0.014 Lux @ (F1.4,AGC ON),0 Lux with IR
Shutter Speed	1/25 (1/30)s to 1/50,000 s
Lens	2.8mm Angle of view: 105.8° (2.8 mm)
Lens Mount	M12
Angle Adjustment	Pan: 0 - 355°, Tilt: 0 - 80°, Rotation: ± 90°
Day & Night	ICR
Wide dynamic range	dWDR
Synchronization	Internal synchronization
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 Analog HD output
S/N Ratio	More than 52dB

► General

Working Temperature/ Humidity	-20°C-60°C(-4°F-140°F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC
Power Consumption	Max. 4.5 W
IR Range	Up to 20 m
Communication	Up the coax(need UTC controller) Protocol: Pelco-C(Coaxitron)
Dimensions	97.8 × 64.4 mm (3.85 × 2.54in)
Weight	300 g (0.66 lb)

► Menu

Scene	Indoor, LOW-LIGHT
Camera ID	On/off (15 characters, position programmable)
AGC	Support
D/N Mode	Smart IR /color/BW/EXT
White Balance	ATW, AWC-SET, Indoor, Outdoor, Manual
Privacy Mask	On/Off, maximum 8 zones
Motion Detection	On/Off, maximum 4 zones
BLC	Support
Anti-flicker	On/off
Language	English
Function	Digital noise reduction and mirror

► Key Features

- HD1080p video output
- Adopt HDTVl Technology
- 2.8mm Wide Angle Lens
- OSD menu, 3D DNR, Smart IR
- Up to 20m IR distance
- Up the Coax(via coaxial cable)
- Digital WDR
- For indoor use only