THX ULTRA2 NINE CHANNEL AMPLIFIER



FEATURES

GENERAL:

• THX Ultra2 Certified

AMPLIFIER:

- 150 Watts per Channel at 8 ohms, 20 Hz-20 kHz, 0.05% THD
- WRAT (Wide Range Amplifier Technology)
- HICC (High Instantaneous-Current Capability)
- Push-Pull Amplification Design with Three-Stage Inverted Darlington Circuitry to Remove Distortion
- All Discrete Output Stage Circuitry
- Massive Toroidal Transformer
- Two Large, Customized, 22,000 μF Capacitors for Effective Power Supply
- Audio-Tuned Reference Capacitors for Each Channel
- Large, Custom-Designed Power Transistors for High Current
- Low-Impedance, Copper Bus Plates for Perfect Ground Potential

CONNECTIONS:

- Gold-Plated XLR Inputs
- Machined Solid Brass RCA Inputs
- Gold-Plated, Color-Coded, Banana Plug-Compatible, Transparent Speaker Posts

MISCELLANEOUS:

- Multi-Zone Capability (up to Zone 3)*
- Bi-Amping Capability*
- 12 V Trigger Input
- Auto Power Down Function
- Flat, High-Rigidity, Anti-Resonant Chassis
- Aluminum Front Panel
- Heavy-Duty Detachable IEC Power Cord
- Optional Rack Mount Kit Available IRK-180-4B

^{*} Depending on A/V Controller.

THX ULTRA2 NINE CHANNEL AMPLIFIER





W2AT

SPECIFICATIONS

AMPLIFIER SECTION

Rated Power Output

20Hz-20kHz 0.5% THD (FTC): 150 W 8Ω 2 ch Driven

Dynamic Power Output: 400 W at 3Ω

300 W at 4Ω

180 W at 8Ω

Frequency Response: 5 Hz - 100 kHz (+1, -3 dB) Signal-to-Noise Ratio: 110 dB (LINE, IHF-A)

Total Harmonic Distortion: 0.05% (Rated Power)

Damping Factor: $60 \text{ at } 8\Omega$

Input Sensitivity & Impedance: 1 V/47 k-ohms (Balanced)

2 V/22 k-ohms (Unbalanced)

Rated Speaker Impedance: $4 \Omega - 16 \Omega$

GENERAL

Power Supply: AC 120 V, 60 Hz Power Consumption: 11.7 Amps


Dimensions (W x H x D): 17 1/8" x 7 13/16" x 17 1/2"


435 x 198.5 x 445 mm

Weight: 50.7 lbs. (23 kg)

Optional Mounting Kit: IRK-180-4

U Dimension: 5U





Due to a policy of continuous product improvement, Integra reserves the right to change specifications and appearance without notice.

02/2010 Printed in the USA