

D8TURBO

HD 1080p Turbo HD Dome Camera

▶ Camera

Image Sensor	1/3" Progressive Scan CMOS
Effective Pixels	1920(H) * 1080(V)
Min. Illumination	0.01Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	1/25 (1/30)s to 1/50,000 s
Lens	2.8mm (3.6mm, 6mm optional) Angle of view: 76.88°(3.6mm), 99.73°(2.8mm), 50.1° (6mm)
Lens Mount	M12
Angle Adjustment	Pan: 0 - 360°, Tilt: 0 - 90°, Rotation: 0 - 360°
Day & Night	ICR
Synchronization	Internal synchronization
Video Frame Rate	25 fps (PAL) / 30 fps (NTSC)
HD Video Output	1 Analog HD output
S/N Ratio	More than 52dB



▶ General

Working Temperature / Humidity	-40°C to 60°C (-40°F to 140°F) Humidity 90% or less (non-condensing)
Power Supply	12VDC
Power Consumption	Max. 3.5W
Weather Proof Ratings	No
IR Range	Up to 20m
Dimensions	φ97.8 × 64.4mm
Weight	300 g (0.66 lb)

▶ Key Features

HD1080P Video Output
Adopt HDTVI Technology
True Day/Night
DNR, SmartIR
20m IR Distance



epcom
POWERED BY HIKVISION

TURBOHD
series