

Kramer's GM/GM and GM/GF computer graphics video cables are high-performance cables with molded 15-pin HD connectors on both ends. They are used for connecting computer graphics video signals between computers or video scalars and plasma, LCD or other popular display technologies

FEATURES

Quality Construction - Highresolution 26 gauge mini coax for video

Easy Installation - Preterminated with molded 15pin HD connectors, gold plated pins and thumbscrews for easy connection

Cable Specs - See Kramer BC3X2T7S for detailed cable specs

Varied Selection of Lengths - Available in 1 to 150ft versions (0.3 to 45.7m)

TECHNICAL SPECIFICATIONS

CONSTRUCTION

Dielectric:	Foam polyethylene with red, green, blue color coding
Shield:	(A) 90% spiral 38AWG tinned copper (B) aluminumfoil/Mylar 25% overlap rate
Inner Jacket:	PVC
Jacket Colors:	Black

DIAMETERS

Dielectric:	0.076in (1.95mm)
Individual Coax:	0.102in (2.6mm)

ELECTRICAL

DC resistance: 45/1000ft (148/km)

Capacitance: 17.3pF/ft (57pF/m)

Attenuation (dB/100ft):
0.5dB @1MHz
1.3dB @5MHz
1.9dB @10MHz
4.0dB @50MHz
5.7dB @100MHz
8.0dB @180MHz
14.0dB @400MHz

Temperature: 68° to 167°F (20° to 75°C)

REGULATORY

CSA: C(UL) CL2

CONFIGURATIONS

C-GM/GM-1	Molded 15-pin HD (M) to 15-pin HD (M) Cable
C-GM/GM-3	Molded 15-pin HD (M) to 15-pin HD (M) Cable
C-GM/GM-6	Molded 15-pin HD (M) to 15-pin HD (M) Cable
C-GM/GM-10	Molded 15-pin HD (M) to 15-pin HD (M) Cable
C-GM/GM-12	Molded 15-pin HD (M) to 15-pin HD (M) Cable
C-GM/GM-15	Molded 15-pin HD (M) to 15-pin HD (M) Cable
C-GM/GM-25	Molded 15-pin HD (M) to 15-pin HD (M) Cable
C-GM/GM-35	Molded 15-pin HD (M) to 15-pin HD (M) Cable
C-GM/GM-50	Molded 15-pin HD (M) to 15-pin HD (M) Cable
C-GM/GM-75	Molded 15-pin HD (M) to 15-pin HD (M) Cable
C-GM/GM-100	Molded 15-pin HD (M) to 15-pin HD (M) Cable
C-GM/GM-125	Molded 15-pin HD (M) to 15-pin HD (M) Cable
C-GM/GM-150	Molded 15-pin HD (M) to 15-pin HD (M) Cable
