



FC-46xI

HDMI Audio DeEmbedder

| HDMI | HDCP Compliant



The FC46xI is a highperformance HDMI audio deembedder. The unit can deembed audio from the HDMI input or from the HDMI output Audio Return channel to S/PDIF, TOSLINK® and analog audio outputs simultaneously

FEATURES

Max. Data Rate - 6.75Gbps (2.25Gbps per graphic channel)

HDCP Compliant

HDTV Compatible

I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling & processing algorithm ensures Plug and Play operation for HDMI systems

HDMI Support - ARC and HDMI Uncompressed Audio Channels

Auto Format Detection - Digital RGB or YPbPr



KRAMER

TECHNICAL SPECIFICATIONS

INPUT:	1 HDMI connector
OUTPUTS:	1 HDMI connector, 1 TOSLINK® optical digital audio connector, 1 S/PDIF digital audio on an RCA connector, 1 unbalanced stereo audio on a 3.5mm mini connector
MAX. DATA RATE:	Supports up to 6.75 Gbps (2.25Gbps per graphic channel), 1080p @60Hz, 36bit Deep Color
COMPLIANCE WITH STANDARDS:	Supports HDMI, HDCP
CONTROLS:	Audio source select button
INDICATOR LEADS:	ON, IN, OUT
POWER CONSUMPTION:	5V DC, 730mA
OPERATING TEMPERATURE:	0° to +40°C (32° to 104°F)
STORAGE TEMPERATURE:	40° to +70°C (40° to 158°F)
HUMIDITY:	10% to 90%, RHL noncondensing
INCLUDED ACCESSORIES:	Power supply
PRODUCT DIMENSION:	12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H
PRODUCT WEIGHT:	0.2kg (0.4lbs) approx
SHIPPING DIMENSION:	15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H
SHIPPING WEIGHT:	0.5kg (1.1lbs) approx
OPTIONS:	Kramer VA-100P-5 10-Port Universal 5V Power Supply , RK-3T 19" rack adapter

