

XFS-1816P

WHAT THIS PRODUCT DOES:

With 16 PoE+ ports and 2 additional Gigabit ports, the Luxul 18 Port/16 PoE+ Managed Switch (XFS-1816P) is an ideal solution for use with a 16 Channel NVR Security System. The 16 Fast Ethernet PoE+ ports ensure that all 16 cameras can be connected while still offering 2 additional Gigabit ports for use as uplinks to your router, main switch, or even directly to the NVR. With a healthy budget of 230W and a max of 30W per port, you'll have sufficient power for even the most demanding projects. The XFS-1816P can be used as a plug and play device, while also offering a simple-to-use interface for remote reboot of connected IP cameras and other PoE management features that ensure optimal benefit from your network.

USE THE XFS-1816P TO:

- ▶ Connect up to 16 IP Cameras or Other PoE-Enabled Devices (Max Output 230 Watts)
- ▶ Add 802.3af/at Gigabit PoE+ Capability to Your Network
- ▶ Remotely Manage and/or Reboot Your PoE-Enabled Devices
- ▶ Enable High Speed LAN Connectivity with Gigabit Uplinks
- ▶ Simply Plug and Play

FEATURES:

- ▶ 16 RJ45 Fast Ethernet Ports with 802.3af/at PoE+
- ▶ 2 Gigabit Uplink Ports
- ▶ 1 Shared Gigabit SFP Port (Combo Port)
- ▶ 230 Watt Power Budget
- ▶ Plug-and-Play Installation with Intuitive Management
- ▶ Simple Power Management of PoE-Enabled Devices
- ▶ Quiet Operation
- ▶ Standard 19" Rack-Mount Metal Case
- ▶ 3 Year Limited Warranty

18-Port/16 PoE+/2 Gig Uplink Smart Switch



XFS-1816P TECHNICAL SPECIFICATIONS

Hardware Features

Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.3ab, IEEE 802.3af, IEEE 802.1D, IEEE 802.3x
Interface	<ul style="list-style-type: none"> ▶ RJ-45 ▶ 10 Base-T: Cat.5 UTP /STP ▶ 100 Base-TX: Cat.5 UTP /STP ▶ 1000Base-T: Cat.5, Cat.5e or Cat.6 UTP/STP (Uplink Only) ▶ Cable Recognition for Straight-through or Crossover Cables
LED	<ul style="list-style-type: none"> ▶ Per Unit: Power ▶ Per Port: Link/Activity, PoE
Power Supply	Internal Switched Power, AC 100-240V, 50-60Hz input
Power Budget	230 Watts Maximum
Power Supply	External Power Adapter
VLAN	<ul style="list-style-type: none"> ▶ 802.1Q Max 4094 VLANs ▶ Port Based VLAN ▶ Supports 1 Management VLAN
Quality of Service (QoS)	<ul style="list-style-type: none"> ▶ 4 Queues per port ▶ Queue Handling: Strict, Weighted Round Robin (WRR) ▶ CoS Based on DSCP, 802.1P and Port-based Priority Queues ▶ Port- based Bandwidth Control
Network Data Transfer Rate	<ul style="list-style-type: none"> ▶ Ethernet: 10Mbps (Half-duplex) ▶ Ethernet: 20Mbps (Full-duplex) ▶ Fast Ethernet: 100Mbps (Half-duplex) ▶ Fast Ethernet: 200Mbps (Full-duplex) ▶ Gigabit Ethernet: 2000Mbps (Full-duplex)
Operating Temperature	32°F to 104°F (0°C to 40°C)
Operating Humidity	10% to 90% (Non-condensing)
Dimensions L x W x H in. (mm)	17.3"(439.5) x 8.25"(209.5) x 1.7"(43.2)
Certification	FCC, CE, RoHS

Warranty:

- ▶ 3 Year Limited Warranty

Minimum System Requirements

- ▶ Suitable Network/PoE Devices
- ▶ Ethernet Cable
- ▶ Internet Connection to View Documentation Online

Package Contents

- ▶ One: 18-Port/16 PoE+/2 Gig Uplink Smart Switch
- ▶ One: Power Cord
- ▶ One: Quick Install Guide
- ▶ Mounting Brackets and Rubber Footpads

All references to speed are for comparison purposes only.

Product specifications, size and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.