MC-WX8751W LCD Projector



Accessories and Lenses		
Supplied Accessories	Remote control, power cord, computer cable, AA batteries x 2, adapter cover, terminal cover, manual CD, user's manual, application CD, security label, HDMI bracket x 2, binder x 2	
Optional Accessories	Wireless adapter (USBWL11N)	
Optional Lenses	7 optional lenses are available, FL710M, USL701, FL701, SL712, ML713, LL704, UL705 (This model ships without a lens)	
Replacement Parts		
Lamp	DT01881M	
Remote Control	HL02805	
Filter	UX40821	

Projection Throw Chart

Screen Size 16:10		Throw E	Distance
Diagonal	Width	Min	Max
30	25	46	77
80	68	120	202
100	85	149	252
150	127	223	378
200	170	297	504
250	212	370	629
300	254	444	755
600	509	887	1508

Throw Ratio: 1.7 - 3.0 : 1 (distance : width) Screen size and throw distance are measured in inches with standard lens ML713.

Projection Lens Chart

Lens	Inches	Meters
FL710M	4.27	0.11
USL701	67 - 87	1.71 - 2.21
FL701	71	1.79
SL712	102 - 154	2.59 - 3.90
ML713	149 - 253	3.79 - 6.41
LL704	244 - 415	6.21 - 10.55
UL705	415 - 705	10.54 - 17.91

Projection distances measured in inches and meters with standard lens and optional lenses when projecting onto a 100" diagonal screen.







MX0668-Rev.2-11/19

MX0688-Rev2-11/19
All specifications subject to change without notice.
3LCD and the 3LCD logo are registered trademarks of the Seiko Epson Corporation. Crestron®, Crestron e-Control®, e-Control®, Crestron Connected®, Fusion RV®, Crestron RoomView® and RoomView™ are trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and other countries. HDMI, the HDMI Logo, and High-Definition Multimedia Interface are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. HDBaseT™ and the HDBaseT Alliance logo are trademarks of the HDBaseT Alliance. All other brand or product names are trademarks or registered trademarks of their respective holders. ©2019 Maxell Corporation of America. All Rights Reserved.

Spe	cifications	
	Projection Technology	3LCD, 3 chip technology
	Resolution	WXGA - 1280 x 800
	White Light Output	7,500 ANSI lumens
	Color Light Output	7,500 ANSI lumens
play	Colors	16.7 million colors
ds	Aspect Ratio	Native 16:10 and 4:3 / 16:9 compatible
	Contrast Ratio	10,000 : 1 (using active IRIS)
	Throw Ratio	Specifications will vary depending on which lens is used with
	(distance : width)	the projector
	Display Size	30" - 600"
uo	Lens	Specifications will vary depending on which lens is used with the projector (This model ships without a lens)
ati	Lamp Wattage	430W
Lens & Operation	Expected Lamp Life*	Approximately 2,000 hours (standard mode) 4,000 hours (Eco mode)
~ර ග	Expected Filter Life**	Approximately 20,000 hours
e	Speaker Output	16W (8W x 2 stereo)
	Keystone	H and V: +/- 5°
	Computer	VGA, SVGA, XGA, WXGA, WXGA+, SXGA, SXGA+, WSXGA+, UXGA, WUXGA, MAC16"
_ ≝	H-Sync	15 kHz - 106 kHz
을	V-Sync	50 Hz - 120 Hz
edι	Composite Video	NTSC, NTSC4.43, PAL, PAL-M, -N, SECAM
Compatibility	Component Video	480i, 480p, 576i, 720p, 1080i, 1080p
ŏ	НДМІ	480i, 480p, 576i, 720p, 1080i, 1080p,
		Computer signal TMDS clock 27 MHz - 150 MHz
	Digital Input	Computer signal TMDS clock 27 MHz - 150 MHz HDMI x 2, HDBaseT x 1, Display Port x 1,
	Digital Input Computer Input	
		HDMI x 2, HDBaseT x 1, Display Port x 1,
	Computer Input	HDMI x 2, HDBaseT x 1, Display Port x 1, 15-pin mini D-sub x 1
	Computer Input Computer Monitor Output	HDMI x 2, HDBaseT x 1, Display Port x 1, 15-pin mini D-sub x 1
S	Computer Input Computer Monitor Output Video Input	HDMI x 2, HDBaseT x 1, Display Port x 1, 15-pin mini D-sub x 1 15-pin mini D-sub x 1
tors	Computer Input Computer Monitor Output Video Input S-Video	HDMI x 2, HDBaseT x 1, Display Port x 1, 15-pin mini D-sub x 1 15-pin mini D-sub x 1 N/A
nectors	Computer Input Computer Monitor Output Video Input S-Video Composite Video	HDMI x 2, HDBaseT x 1, Display Port x 1, 15-pin mini D-sub x 1 15-pin mini D-sub x 1 N/A RCA jack x 1
onnectors	Computer Input Computer Monitor Output Video Input S-Video Composite Video Component Video	HDMI x 2, HDBaseT x 1, Display Port x 1, 15-pin mini D-sub x 1 15-pin mini D-sub x 1 N/A RCA jack x 1 15-pin mini D-sub shrink x 1 (shared with computer input)
Connectors	Computer Input Computer Monitor Output Video Input S-Video Composite Video Component Video Audio Input	HDMI x 2, HDBaseT x 1, Display Port x 1, 15-pin mini D-sub x 1 15-pin mini D-sub x 1 N/A RCA jack x 1 15-pin mini D-sub shrink x 1 (shared with computer input) 3.5 mm stereo mini jack x 1, 2 RCA x 1
Connectors	Computer Input Computer Monitor Output Video Input S-Video Composite Video Component Video Audio Input Audio Output	HDMI x 2, HDBaseT x 1, Display Port x 1, 15-pin mini D-sub x 1 15-pin mini D-sub x 1 N/A RCA jack x 1 15-pin mini D-sub shrink x 1 (shared with computer input) 3.5 mm stereo mini jack x 1, 2 RCA x 1 3.5 mm stereo mini jack x 1
Connectors	Computer Input Computer Monitor Output Video Input S-Video Composite Video Component Video Audio Input Audio Output Network LAN Wired	HDMI x 2, HDBaseT x 1, Display Port x 1, 15-pin mini D-sub x 1 15-pin mini D-sub x 1 N/A RCA jack x 1 15-pin mini D-sub shrink x 1 (shared with computer input) 3.5 mm stereo mini jack x 1, 2 RCA x 1 3.5 mm stereo mini jack x 1 RJ-45 jack x 1
Connectors	Computer Input Computer Monitor Output Video Input S-Video Composite Video Component Video Audio Input Audio Output Network LAN Wired Network LAN Wireless	HDMI x 2, HDBaseT x 1, Display Port x 1, 15-pin mini D-sub x 1 15-pin mini D-sub x 1 N/A RCA jack x 1 15-pin mini D-sub shrink x 1 (shared with computer input) 3.5 mm stereo mini jack x 1, 2 RCA x 1 3.5 mm stereo mini jack x 1 RJ-45 jack x 1 USB-A, IEEE802.11 b/g/n - optional wireless adapter required
Connectors	Computer Input Computer Monitor Output Video Input S-Video Composite Video Component Video Audio Input Audio Output Network LAN Wired Network LAN Wireless HDBaseT	HDMI x 2, HDBaseT x 1, Display Port x 1, 15-pin mini D-sub x 1 15-pin mini D-sub x 1 N/A RCA jack x 1 15-pin mini D-sub shrink x 1 (shared with computer input) 3.5 mm stereo mini jack x 1, 2 RCA x 1 3.5 mm stereo mini jack x 1 RJ-45 jack x 1 USB-A, IEEE802.11 b/g/n - optional wireless adapter required RJ-45 jack x 1
Connectors	Computer Input Computer Monitor Output Video Input S-Video Composite Video Component Video Audio Input Audio Output Network LAN Wired Network LAN Wireless HDBaseT USB	HDMI x 2, HDBaseT x 1, Display Port x 1, 15-pin mini D-sub x 1 15-pin mini D-sub x 1 N/A RCA jack x 1 15-pin mini D-sub shrink x 1 (shared with computer input) 3.5 mm stereo mini jack x 1, 2 RCA x 1 3.5 mm stereo mini jack x 1 RJ-45 jack x 1 USB-A, IEEE802.11 b/g/n - optional wireless adapter required RJ-45 jack x 1 Type A x 1 (wireless network)
	Computer Input Computer Monitor Output Video Input S-Video Composite Video Component Video Audio Input Audio Output Network LAN Wired Network LAN Wireless HDBaseT USB Wired Remote Control	HDMI x 2, HDBaseT x 1, Display Port x 1, 15-pin mini D-sub x 1 15-pin mini D-sub x 1 N/A RCA jack x 1 15-pin mini D-sub shrink x 1 (shared with computer input) 3.5 mm stereo mini jack x 1, 2 RCA x 1 3.5 mm stereo mini jack x 1 RJ-45 jack x 1 USB-A, IEEE802.11 b/g/n - optional wireless adapter required RJ-45 jack x 1 Type A x 1 (wireless network) 3.5 mm stereo mini jack (IN/OUT)
	Computer Input Computer Monitor Output Video Input S-Video Composite Video Component Video Audio Input Audio Output Network LAN Wired Network LAN Wireless HDBaseT USB Wired Remote Control Control Terminals	HDMI x 2, HDBaseT x 1, Display Port x 1, 15-pin mini D-sub x 1 N/A RCA jack x 1 15-pin mini D-sub shrink x 1 (shared with computer input) 3.5 mm stereo mini jack x 1, 2 RCA x 1 3.5 mm stereo mini jack x 1 RJ-45 jack x 1 USB-A, IEEE802.11 b/g/n - optional wireless adapter required RJ-45 jack x 1 Type A x 1 (wireless network) 3.5 mm stereo mini jack (IN/OUT) 9-pin D-sub x 1 (RS-232 control)
	Computer Input Computer Monitor Output Video Input S-Video Composite Video Component Video Audio Input Audio Output Network LAN Wired Network LAN Wireless HDBaseT USB Wired Remote Control Control Terminals Power Supply	HDMI x 2, HDBaseT x 1, Display Port x 1, 15-pin mini D-sub x 1 N/A RCA jack x 1 15-pin mini D-sub shrink x 1 (shared with computer input) 3.5 mm stereo mini jack x 1, 2 RCA x 1 3.5 mm stereo mini jack x 1 RJ-45 jack x 1 USB-A, IEEE802.11 b/g/n - optional wireless adapter required RJ-45 jack x 1 Type A x 1 (wireless network) 3.5 mm stereo mini jack (IN/OUT) 9-pin D-sub x 1 (RS-232 control) AC90-132V / AC198-264V, 50/60Hz
	Computer Input Computer Monitor Output Video Input S-Video Composite Video Component Video Audio Input Audio Output Network LAN Wired Network LAN Wireless HDBaseT USB Wired Remote Control Control Terminals Power Supply Power Consumption	HDMI x 2, HDBaseT x 1, Display Port x 1, 15-pin mini D-sub x 1 N/A RCA jack x 1 15-pin mini D-sub shrink x 1 (shared with computer input) 3.5 mm stereo mini jack x 1, 2 RCA x 1 3.5 mm stereo mini jack x 1 RJ-45 jack x 1 USB-A, IEEE802.11 b/g/n - optional wireless adapter required RJ-45 jack x 1 Type A x 1 (wireless network) 3.5 mm stereo mini jack (IN/OUT) 9-pin D-sub x 1 (RS-232 control) AC90-132V / AC198-264V, 50/60Hz 580W / 560W
	Computer Input Computer Monitor Output Video Input S-Video Composite Video Component Video Audio Input Audio Output Network LAN Wired Network LAN Wireless HDBaseT USB Wired Remote Control Control Terminals Power Supply Power Consumption Operating Temperature	HDMI x 2, HDBaseT x 1, Display Port x 1, 15-pin mini D-sub x 1 N/A RCA jack x 1 15-pin mini D-sub shrink x 1 (shared with computer input) 3.5 mm stereo mini jack x 1, 2 RCA x 1 3.5 mm stereo mini jack x 1 RJ-45 jack x 1 USB-A, IEEE802.11 b/g/n - optional wireless adapter required RJ-45 jack x 1 Type A x 1 (wireless network) 3.5 mm stereo mini jack (IN/OUT) 9-pin D-sub x 1 (RS-232 control) AC90-132V / AC198-264V, 50/60Hz 580W / 560W 32°F - 113°F (0°C - 45°C)
	Computer Input Computer Monitor Output Video Input S-Video Composite Video Component Video Audio Input Audio Output Network LAN Wired Network LAN Wireless HDBaseT USB Wired Remote Control Control Terminals Power Supply Power Consumption Operating Temperature Dimensions (W x D x H)	HDMI x 2, HDBaseT x 1, Display Port x 1, 15-pin mini D-sub x 1 N/A RCA jack x 1 15-pin mini D-sub shrink x 1 (shared with computer input) 3.5 mm stereo mini jack x 1, 2 RCA x 1 3.5 mm stereo mini jack x 1 RJ-45 jack x 1 USB-A, IEEE802.11 b/g/n - optional wireless adapter required RJ-45 jack x 1 Type A x 1 (wireless network) 3.5 mm stereo mini jack (IN/OUT) 9-pin D-sub x 1 (RS-232 control) AC90-132V / AC198-264V, 50/60Hz 580W / 560W 32°F - 113°F (0°C - 45°C) 19.6" x 16.8" x 6.1" (without lens)
Ratings & Warranty Connectors	Computer Input Computer Monitor Output Video Input S-Video Composite Video Component Video Audio Input Audio Output Network LAN Wired Network LAN Wireless HDBaseT USB Wired Remote Control Control Terminals Power Supply Power Consumption Operating Temperature Dimensions (W x D x H) Weight	HDMI x 2, HDBaseT x 1, Display Port x 1, 15-pin mini D-sub x 1 N/A RCA jack x 1 15-pin mini D-sub shrink x 1 (shared with computer input) 3.5 mm stereo mini jack x 1, 2 RCA x 1 3.5 mm stereo mini jack x 1 RJ-45 jack x 1 USB-A, IEEE802.11 b/g/n - optional wireless adapter required RJ-45 jack x 1 Type A x 1 (wireless network) 3.5 mm stereo mini jack (IN/OUT) 9-pin D-sub x 1 (RS-232 control) AC90-132V / AC198-264V, 50/60Hz 580W / 560W 32°F - 113°F (0°C - 45°C) 19.6" x 16.8" x 6.1" (without lens) Approximately 24.5 lbs



Actual filter life will vary by individual filter based on environmental conditions, selected operating mode, user settings and usage. Hours of average filter life specified are not guaranteed and do not constitute part of the product warranty











Toll Free: 1.800.377.5887 Web: www.maxellproav.com







