

P-2 Wash Light

Specifications		
Optics	Light source	18 x High power 10W RGBW LEDs
	LEDs expected lifetime	50,000 hours*
	Interchangeable lens option	15°, 21° & 43°
Photometric	Light output	10,100 lumen (43° lens)
	Efficacy	51 lm/W
Features	Pan/Tilt	0° / 180°
	LED Panel	3 individual controllable segments
Electrical	AC Power nominal	100 - 277V 50/60Hz
	AC Power max rating	90 - 305V 50/60Hz
	Maximum power consumption	275 W (all LEDs on)
	Typical power consumption	200 W (all LEDs on)
	Power factor	0.98 PF (230 V)
Programming and Control	Protocol	USITT DMX512 A
	Setting and addressing	RDM Stand alone mode Oled graphical display / 4 buttons Software upgradable via Uploader cable (P/N:83062011)
	DMX channels	3, 6, 9, 12, 15 or 22
Physical	Dimensions (L x H x W)	334 x 223 x 105 mm (13,2 x 8,8 x 4.1 in)
	Weight	6.1 kg (13.4 lbs.)
	Material	Aluminium
	Lens	PE and tempered glas front
	IP class	IP65
Installation	Orientation	Any
	Rigging possibilities	Floor stand (included) or hanging (Omega Clamp included)
	Safety features	Bottom mount for Safety wire
Thermal	Temperature range, Operating	-10° to +40°C (14° to +104°F)
	Temperature range, Start-up	-10° to +40°C (14° to +104°F)
	Humidity (max.)	98%
	Cooling	Active, forced air, temperature-regulated, low noise
Connections	DMX data in/out	IP65 Neutrik HD locking XLR 5-pin cable 0.5m, for DMX in and out Power cable 1m with bare ends
Certified to	CSA E60598-1:02, Ed: 2 CSA-E598-2-17-98, Ed: 1	
Conforms to	UL Std. 1573 2014/35/EU: Low Voltage Directive 2014/30/EU: EMC Directive RoHS2 Directive	EN 60598-1, EN 60598-2-17, EN 62471, EN 60529 EN 55103-1, EN 55103-2, EN 55015, EN 61547, EN 61000-3-2, EN 61000-3-3 2011/65/EU
Included Items	Included Items	Floor Stand (incl. screws) 1 pcs Omega bracket User manual Neopren pouch
Fixtures and Accessories	Fixtures Cables Lens/s Bracket Barndoor Flight case	Order no: 80030528 - P-2 Wash, 43deg, Std, BL
		Order no: 80030543 - P-2 Wash, 43deg, Std, WH
		Order no: 80030591 - P-2 Wash, 43deg, Std, CU
		Order no: 80030526 - P-2 Wash, 21deg, Std, BL
		Order no: 80030544 - P-2 Wash, 21deg, Std, WH
		Order no: 80030592 - P-2 Wash, 21deg, Std, CU
		Order no: 80030529 - P-2 Wash, 15deg, Std, BL
Order no: 80030545 - P-2 Wash, 15deg, Std, WH		
Order no: 80030593 - P-2 Wash, 15deg, Std, CU		
Order no: 83062011 - SGM USB uploader cable		
Order no: 83061134 - P-2, Lens kit (43°)		
Order no: 83061133 - P-2, Lens kit (21°)		
Order no: 83061132 - P-2, Lens kit (15°)		
Order no: 83060602 - Omega bracket		
Order no: 83061127 - Accessory Holder P-2 series		
Order no: 83061129 - Barndoor 4-way, P-2/Q-2 series		
Order no: 83061130 - Barndoor 8-way, P-2/Q-2 series		
Order no: 83061131 - Color frame, P-2/Q-2 series		
Order no: 82051503 - Flight case for 4 pcs of P-2/Q-2 incl. Barndoors		

*Goniometer Scan / Ocean optics / Viso Systems Light Spion TM

Figures provided by manufacturer and obtained under manufacturer's test conditions

BL = Black (RAL 9004)

WH = White (RAL 9010)

CU = Custom Color (Any RAL color)