

RMUBRKT1/WBPWR-50 Pan-and-Tilt Bracket



Product Description

The RMUBRKT1/WBPWR-50 are pan-and-tilt brackets that attach to the rear panel threaded inserts of all RoomMatch® Utility loudspeakers, F1 Model 812 Active and Passive loudspeakers as well as the Panaray 402 Series IV. These brackets allow both pitch and yaw adjustments to enable flexible mounting options. WBPWR-50 is outdoor rated for use with outdoor installations of the Panaray 402 Series IV loudspeaker only. Indoor installations of Panaray 402 Series IV can use either bracket.

RMUBRKT1/WBPWR-50 fit the 4x M8 threaded inserts (127 x 70 mm) on the rear panel of the F1 Model 812, Panaray® 402® Series IV, RMU208, RMU206 and RMU108 models, as well as the 2x M8 threaded inserts (75 mm spacing) on the rear panel of the RMU105 model.



Key Features

- Fits all RMU loudspeakers, F1 Loudspeakers, and Panaray 402 Series IV
- Horizontal or vertical mounting (RMU105, vertical only)
- Convenient hook-and-lock method for easy mounting
- Available in indoor (RMUBRKT1) and outdoor models (WBPWR-50)

Technical Specifications

Mechanical			
Angle of inclination		0° to 30°	
Speaker plate		15.0 cm x 8.8 cm (5.9" x 3.5")	
Wall plate		16.0 cm x 9.0 cm (6.3" x 3.6")	
Material		Steel	
Maximum load capacity		22.7 kg (50.0 lb)	
Swivel		90° rotatable speaker plate	
Wall clearance		10.9 cm (4.3")	
Weight		1.2 kg (2.6 lb)	
General			
Compatible with		RMU208, RMU206, RMU108, RMU105, F1 Model 812 (active and passive), Panaray 402 Series IV	
Product codes		738453-0110 – RMUBRKT1 RMU Pan-and-Tilt Bracket, Black 738453-0210 – RMUBRKT1 RMU Pan-and-Tilt Bracket, White 738453-0120 – WBPWR-50B Outdoor, for use with Panaray 402 Series IV only, Black 738453-0220 – WBPWR-50W Outdoor, for use with Panaray 402 Series IV only, White	
Pitch and Yaw adjustments with loudspeakers			
	Orientation	Pitch	Yaw
RMU208	Horizontal	0 – 30°, infinite resolution	±15°, infinite resolution
	Vertical	0 – 15°, infinite resolution	±60°, infinite resolution
RMU206	Horizontal	0 – 30°, infinite resolution	±20°, infinite resolution
	Vertical	0 – 20°, infinite resolution	±50°, infinite resolution
RMU108	Horizontal	0 – 30°, infinite resolution	+20° thru –30 or +30 thru –20 based on bracket orientation
	Vertical	0 – 25°, infinite resolution	±55°, infinite resolution
RMU105	Vertical, only	0 – 25°, infinite resolution	±55°, infinite resolution
F1 Model 812	Horizontal	0 – 30°, infinite resolution	±15°, infinite resolution
	Vertical	0 – 15°, infinite resolution	±45°, infinite resolution
402 Series IV	Horizontal	0 – 30°, infinite resolution	+50° thru –10 or +10 thru –50 based on bracket orientation
	Vertical	0 – 30°, infinite resolution	±55°, infinite resolution