

# SOUNDBAR


## SB46 M AND SB46 L



### Product Family Overview

Sonance, the company that invented the in-wall and in-ceiling speaker category, introduces the world's first adjustable-width Soundbar. Both models feature a patent-pending design that allows the installer to adjust the width to perfectly match any display between 50" and 80" (127cm to 203cm). The Sonance Soundbars ensure exact alignment every time; even if the

display is changed. Developed utilizing state-of-the-art design and modeling software and featuring driver technology used in Sonance's next generation Visual Performance® Series, these LCR configuration Soundbars offer incredible sonic performance, while the passive design allows the use of any high quality amplifier or AV receiver to deliver the best solution for their client.



Coaxial tweeter and midrange & dual high excursion woofers.

### Features and Benefits

#### Adjustable width design (patent pending)

- Simple width adjustment
- Two models perfectly match any display from 50" to 80" (127cm to 203cm)
- 2 9/16" (65mm) shallow design

#### Unprecedented sonic performance

- Passive LCR design
- Each channel features
  - Dual 4 1/2" Kevlar + Nomex laminated cone woofers
  - Coaxial 1" powder coated aluminum dome tweeter with 4" Kevlar + Nomex midrange

#### Extruded aircraft grade aluminum enclosure

#### Perforated metal grilles

#### All mounting hardware included

- Key hole wall mounts
- Flat VESA display mount
- Recessed VESA display mount
- Rubber feet for table top mount


### Dimensions

#### SB46 M

Height: 5 9/32" (134mm)  
Depth: 2 9/16" (65mm)  
Adjustable Width: 43 7/8" to 59 5/8" (1114mm to 1514mm)  
Display Size Range: 50" to 65" diagonal (127cm to 165cm)

#### SB46 L

Height: 5 9/32" (134mm)  
Depth: 2 9/16" (65mm)  
Adjustable Width: 61 1/2" to 77 5/16" (1562mm to 1964mm)  
Display Size Range: 70" to 80" diagonal (178cm to 203cm)






## SPECIFICATIONS


### SB46 M

### SB46 L

SKU	93086	93087
<b>Tweeter</b>	Three - 1" (25mm) powder coated aluminum dome, Ferrite-d-voice, cylindrical	Three - 1" (25mm) powder coated aluminum dome, Ferrite-d-voice, cylindrical
<b>Midrange</b>	Three - 4" (102mm) Kevlar / Nomex laminated cone with a rubber surround	Three - 4" (102mm) Kevlar / Nomex laminated cone with a rubber surround
<b>Woofer</b>	Six - 4 1/2" (114mm) Kevlar / Nomex laminated cone with a rubber surround	Six - 4 1/2" (114mm) Kevlar / Nomex laminated cone with a rubber surround
<b>Frequency Response</b>	90Hz - 20kHz ±3dB	90Hz - 20kHz ±3dB
<b>Impedance</b>	8 ohms nominal; 6 ohms minimum	8 ohms nominal; 6 ohms minimum
<b>Recommended Power</b>	50 watts minimum; 150 watts maximum	50 watts minimum; 150 watts maximum
<b>Sensitivity</b>	88dB SPL (2.83V/1 meter)	88dB SPL (2.83V/1 meter)
<b>Grille</b>	Perforated steel	Perforated steel
<b>Height x Depth</b>	5 1/32" x 2 1/16" (134mm x 85mm)	5 1/32" x 2 1/16" (134mm x 85mm)
<b>Adjustable Width</b>	43 7/8" to 59 5/8" (1114mm to 1514mm)	61 1/2" to 77 5/16" (1562mm to 1964mm)
<b>Display Diagonal Size Range</b>	58" - 65" (127cm to 165cm)	78" - 88" (178cm to 203cm)
<b>Product Weight</b>	21 lbs. (9.5kg) each	26 lbs. (11.8kg) each
<b>Shipping Weight</b>	38 lbs. (13.6kg) each	35 lbs. (15.9kg) each



Mounting Option 1: Bracket Wall Mount



Mounting Option 2: Table Top

Mounting Option 3: Key Hole Wall Mount

For mounting option applications, see detailed installation sheet at: [www.sonance.com/soundbar](http://www.sonance.com/soundbar)

## Associated Products

VP46R SST/SUR

93023



i12 Cabinet Subwoofer

93358



VP66R SST/SUR

93025



i10 Cabinet Subwoofer

93357



VPSUB

93352



i8 Cabinet Subwoofer

93356



DSP 8-130 MKII Amplifier

93331



## LIMITED WARRANTY

Sonance warrants to the first end-user purchaser that this Sonance-brand product ("Product"), when purchased from an authorized Sonance Dealer/Distributor, will be free from defective workmanship and materials for five (5) years, except for the grille, which is warranted for one (1) year. Sonance will at its option and expense either repair the defect or replace the Product with a new or remanufactured Product or a reasonable equivalent. **Please visit our website and owner's e-Manual for complete warranty and exclusion information.**



©2014 Sonance. All rights reserved.

Sonance and Visual Performance are registered trademarks of Dana Innovations.

Due to continuous product improvement, all features and specifications are subject to change without notice. For the latest Sonance product specification information visit our website: [www.sonance.com](http://www.sonance.com)

SONANCE • 991 Calle Amanecer • San Clemente, CA 92673 USA

(949) 492-7777 • FAX: (949) 361-5151 • Technical Support: (949) 492-7777

[www.sonance.com](http://www.sonance.com)