# PRO PLUGS

SS-6 / SS-6B / SS-6B-Pro / PlugLOCK / ACX-25



Whether it's on-stage or in the studio, Furman Pro Plugs give you the protection you need. With surge protection, noise filtration, and diagnostic lighting, you can trust Furman Pro Plugs for reliable, clean, and protected power. Our products have saved billions of dollar's worth of equipment from power problems, and our innovative technologies maximize system performance.



Six outlet power conditioners with standard surge protection, EMI/RFI filtration, heavy duty steel construction, and 15 ft, power cords.

The SS-6B-Pro includes the Furman EVS (Extreme Voltage Shutdown) technology that will disconnect the power conditioner from the AC mains to protect your connected equipment as well as itself. The high shutdown is set at 140 Vac +/- 5% while the low shutdown is set at 95 Vac +/- 5%.

## **POWER CONDITIONERS**

**SS-6** 












Surge Protection



RFI/EMI Filtration

SS-6B



SS-6B-Pro



15A Rating

Diagnostic Lights

6 Outlets

Standard Level





### POWER DISTRIBUTION UNITS



## **PlugLOCK**

Lock your plugs and transformers in place, ensuring you never get disconnected from your power source



ACX-25

Surge Protection RFI/EMI Filtration

Discreet, 25 ft. power cord provides ultimate durability and longevity





5 Outlets











### **POWER CONDITIONERS**

#### **SS-6**

#### SS-6B

#### SS-6B-Pro

AC Protection Technology	Standard spike and surge protection UL VPR:400V, UL Nominal	Standard spike and surge protection UL VPR:400V, UL Nominal	Standard spike and surge protection UL VPR:400V, UL Nominal
Signal Pulse Energy Dissipation	540 Joules	540 Joules	540 Joules
Filtration Technology	Standard level RFI/EMI filtration Filter: -20dB Min, 100kHz – 1MHz	Standard level RFI/EMI filtration Filter: -20dB Min, 100kHz – 1MHz	Standard level RFI/EMI filtration Filter: -20dB Min, 100kHz – 1MHz
Under-Voltage Shutoff	_	_	95VAC +/- 5%
Over-Voltage Shutoff	_	_	140VAC +/- 5%
Dimensions	2.5"W x 1.5"D x 14.5"H	3.5"W x 1.5"D x 9.5"H	3.5"W x 1.5"D x 9.5"H
Weight	2.52lbs	2.64lbs	2.64lbs
AC Power Cord	15ft. captive cord (14AWG)	15ft. captive cord (14AWG)	15ft. captive cord (14AWG)
Outlets	6	6	6
Line Voltage	120V	120V	120V
Current Rating	15 amps	15 amps	15 amps
Safety Listing	cULus	cULus	cULus
Warranty	1 year	1 year	1 year







## **POWER DISTRIBUTION UNITS**

## **PlugLOCK**

**ACX-25** 

2.3"W x 2.5"D x 12.6"H	_
2.125lbs	3lbs
5ft. captive cord (14AWG)	25ft. (14AWG)
5	3
120V	120V
15 amps	15 amps
cCSAus	cULus
1 year	1 year
	2.125lbs  5ft. captive cord (14AWG)  5  120V  15 amps  cCSAus



#### **Product Video**



To find your local Furman Dealer or Regional Sales Representative, please visit:

www.FurmanPower.com