



KRAMER

TP-580T

4K60 4:2:0 HDMI HDCP 2.2 Transmitter with
RS-232 & IR over Long-Reach HDBaseT

| HDMI | HDCP Compliant | HDBaseT
| 4K/60 UHD (4:2:0)



TP-580T is a high-performance, long-reach HDBaseT transmitter for 4K60Hz (4:2:0) HDMI, RS-232 and IR signals over twisted pair. The TP-580T converts all input signals into the transmitted HDBaseT signal. It extends video signals to up to 40m (130ft) over CAT copper cables at up to 4K@60Hz (4:2:0) 24bpp video resolution and provides even further reach for lower HD video resolutions

FEATURES

High Performance Standard Extender - Professional HDBaseT extender for providing long-reach signals over twisted-pair copper infrastructures. TP-580T is a standard extender that can be connected to any market-available HDBaseT-compliant extension product. For optimum extension reach and performance, use recommended Kramer cables

HDMI Signal Extension - HDMI 2.0 and HDCP 2.2 compliant. Supports deep color, x.v.Color™, lip sync, HDMI uncompressed audio channels, Dolby TrueHD, DTS-HD, 2K, 4K, and 3D. EDID and CEC signals are passed through from the source to the display

I-EDIDPro™ Kramer Intelligent EDID Processing™ - Intelligent EDID handling, processing and pass-through algorithm that ensures Plug and Play operation for HDMI source and display systems

Multi-channel Audio Extension - Up to 32 channels of digital stereo uncompressed signals for supporting studio-grade surround sound

Bidirectional RS-232 Extension - Serial interface data flows in both directions, allowing data transmission and device control

Bidirectional Infrared Extension - IR interface data flows in both directions, allowing remote control of peripheral devices located at either end of the extended line

Cost-effective Maintenance - Status LED indicators for HDMI and HDBT ports facilitate easy local maintenance and troubleshooting. Local firmware upgrade via RS-232 connection and the K-Upload tool ensures lasting, field-proven deployment

Easy Installation - Compact DigiTOOLS™ fan-less enclosure for dropped-ceiling mounting, or side-by-side mounting of 3 units in a 1U rack space with the optional RK-3T rack adapter



TECHNICAL SPECIFICATIONS

| | |
|------------------------|---|
| INPUTS: | 1 HDMI on an HDMI connector |
| OUTPUTS: | 1 HDBT on an RJ-45 female connector |
| PORTS: | 1 IR on a 3.5mm mini jack for IR link extension, 1 RS-232 on a 9-pin D-sub connector for serial link extension and device firmware upgrade |
| EXTENSION LINE: | HDBaseT 1.0 compliant; Up to 40m (130ft) at 4K @60Hz (4:2:0); up to 70m (230ft) at full HD (1080p @60Hz 36bpp); Note: When using Kramer HDBaseT cables |
| VIDEO: | Up to 10.2Gbps bandwidth (3.4Gbps per graphic channel) Up to 4K UHD @60Hz (4:2:0) 24bpp resolution HDMI 2.0 and HDCP 2.2 signal compliance |
| EXTENDED RS-232: | 300 to 115200 baud rate |
| CONTROL RS-232: | 115200 baud rate |
| POWER SOURCE: | 12V DC, 2A |
| POWER CONSUMPTION: | 12V DC, 275mA |
| ENCLOSURE: | Tools size, Aluminium type |
| COOLING: | Convection ventilation |
| OPERATING TEMPERATURE: | 0° to 40°C (32° to 104°F) |
| STORAGE TEMPERATURE: | -40° to +70°C (-40° to 158°F) |
| HUMIDITY: | 10% to 90%, RHL non-condensing |
| PRODUCT DIMENSION: | 12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H |
| PRODUCT WEIGHT: | 0.2kg (0.4lbs) approx |
| SHIPPING DIMENSION: | 15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H |
| SHIPPING WEIGHT: | 0.7kg (1.6lbs) approx |
| INCLUDED ACCESSORIES: | Power supply unit |

