

TX-SR444 7.1-Channel A/V Receiver



















Thrilling Dolby Atmos Cinema at an Unbeatable Price

The TX-SR444 is powerful and versatile. It can pass 4K video to your display via HDMI® thanks to HDCP 2.2 compliance. Connection and setup is easy with the rear panel graphical hook-up instructions. AccuEQ room calibration adjusts the audio to suit your listening space and speaker system. And there's also a useful Quick Setup button on the remote to adjust settings without pausing the program. With high-current Wide Range Amplification Technology under the hood, the TX-SR444 receiver delivers sound with power and clarity. With almost 70 years of audio engineering experience behind it, this Onkyo receiver provides the best possible audio performance with the latest features and highest build quality available for a very modest investment.

• 115 W/Ch (6 Ohms, I kHz, 0.9% THD, I Channel Driven, FTC);

H.C.P.S. (High Current Power Supply) Massive High Power Transformer

PLL (Phase Locked Loop) Jitter-Cleaning Circuit Technology for

HDMI® Support for 4K/60 Hz and 4:4:4 Color Space,
Audio Return Channel, DeepColor™, x.v.Color™, LipSync,
Dolby Atmos®, Dolby® TrueHD, DTS-HD Master Audio™, DVD Audio, Super Audio CD, Multichannel PCM, and CEC

65 W/Ch (8 Ohms, 20 Hz–20 kHz, 0.7% THD, 2 Channels Driven,

HIGHLIGHTS

- Supports Dolby Atmos up to 5.1.2 Channels
- 115 W per Channel
- HDMI® 4 In / I Out (4K UltraHD / 4:4:4 / HDCP 2.2)
- True Driving Power from Discrete Amp Circuits
- Bluetooth Wireless Audio Streaming
- · Easy Configuration Rear Panel
- AccuEQ Room Acoustic Calibration
- · HDMI Up-Conversion to One Cable

ADVANCED FEATURES

- 4K/60 Hz-Capable HDMI® Terminals for UltraHD Entertainment, including 4:4:4 Color Space
- Bluetooth Version 2.1 + EDR Capability (Compatible Profile: A2DP v1.2, AVRCP v1.3)
- Advanced Music Optimizer to Improve Compressed Digital Audio Quality (Bluetooth Audio Included)
- Phase-Matching Bass Boost for Deep Bass and Clear Mid-Range Zone B Output for Distributed Audio Playback in Another Room

- •TI Burr-Brown 192 kHz/24-bit DAC for All Channels Advanced 32-bit DSP Chip • 4 DSP Modes for Gaming: Rock, Sports, Action, and RPG
- Theater-Dimensional Virtual Surround Function
- CinemaFILTERⁿ
- Direct Mode
- Double Bass Function
- Non-Scaling Configuration

AMPLIFIER FEATURES

• Discrete Output Stage Circuitry

PROCESSING FEATURES

Dolby Atmos® Decoding

• WRAT (Wide Range Amplifier Technology)

FTC)

· A-Form Listening Mode Memory

CONNECTION FEATURES

- 4 HDMI® Inputs and I Output
- USB Port (Rear) for Powering Media Streaming Sticks (5 V, I A)
- 2 Component Video Inputs (Rear)
- 3 Composite Video Inputs (I Front/2 Rear)
- 3 Digital Audio Inputs (2 Optical and I Coaxial)
- 7 Analog Audio Inputs (I Front/6 Rear)
- Subwoofer Pre-Out
- I/4" Headphone Jack

OTHER FEATURES

- Crossover Adjustment for Each Channel (40/50/60/70/80/90/100/120/150/200 Hz)
- A/V Sync Control (Up to 500 ms in 10 ms Steps at 48 kHz)
- · Overlaid On-Screen Display (OSD) via HDMI with Quick Set-Up
- HDMI Passthrough Function
- Tone Control (Bass/Treble) for Front L/R Channels
- 3-Mode Display Dimmer (Normal/Dim/Dimmer)
- 40 FM/AM Random Presets
- RIHD (Remote Interactive Over HDMI) for System Control
- Full-Function RI (Remote Interactive) Remote Control

TX-SR444 7.1-Channel A/V Receiver

Extraordinary Dolby Atmos®

Dolby Atmos transports you into an extraordinary surround sound experience with captivating, multidimensional sound objects that fill your room and flow all around you. This 7.1-channel receiver can power a 5.1.2-channel Dolby Atmos speaker setup: 5.1 standard surround configuration plus two in-ceiling or height channels: 5.1.2.



HDMI® 4 In / I Out for UltraHD

The latest HDMI specification and HDCP 2.2 compatibility support the latest formats and technologies planned for Hollywood content. This latest HDMI spec offers a significant increase in bandwidth (up to 18Gbps) to support new features such as 4K@50/60 (2160p), which is 4 times the clarity of 1080p/60 video resolution, and 4:4:4 color space



HDCP2.2

True Power from Discrete Amplifiers

Discrete Amps deliver high instantaneous current to increase speaker control for accurate and dynamic audio reproduction. This precise power is the cornerstone of Onkyo's amplification philosophy.



Bluetooth Audio Streaming

Stream virtually any audio from your smartphone, tablet, or PC to your home theater for clear and powerful sound.



Easy Connection Guide on Back Panel

Connections to speakers and external devices are illustrated and clearly labeled on the back panel.



AccuEQ Room Acoustic Calibration

AccuEO measures and corrects speaker distances, output levels, crossover frequencies, and frequency response from one quick and easy listening position to ensure clear and balanced





HDMI Video Up-Conversion

Only one wire! Every video signal is converted and sent to your TV through one HDMI cable.

Ready for Streaming Media Devices

The handy USB port supplies power to streaming media players. Keep up with your video subscription services and other programs streamed from the Internet.

SPECIFICATIONS

Amplifier Section

Power Output	
All Channels	115 W/Ch (6 Ohms, 1 kHz, 0.9% THD,
	I Channel Driven, FTC)
	65 W/Ch (8 Ohms, 20 Hz–20 kHz, 0.7%
	THD, 2 Channels Driven, FTC)
Dynamic Power	I 60 W (3 Ohms, Front)
	125 W (4 Ohms, Front)
	85 W (8 Ohms, Front)
THD+N (Total Harmor	nic Distortion + Noise)
,	0.08% (20 Hz-20 kHz, Half Power)
Damping Factor	Over 40 (Front, 1 kHz, 8 Ohms)
Input Sensitivity and Im	pedance
	200 mV/47 k-ohms (Line)
Rated RCA Output Lev	el and Impedance
	IV /470 Ohms (Subwoofer Pre Out)
Frequency Response	10 Hz-100 kHz/+1 dB, -3 dB (Direct Mode)
Tone Control	±10 dB, 20 Hz (Bass)
	±10 dB, 20 kHz (Treble)

Signal-to-Noise Ratio Speaker Impedance Video Section

Input Sensitivity/Output Level and Impedance		
Video	I.0 Vp-p/75 Ohms (Component Y)	
	0.7 Vp-p/75 Ohms (Component PB/CB, PR/CR)	
	I OVp_p/75 Ohms (Composite)	

100 dB (Line, IHF-A)

Component Video Frequency Response

	3 1 12 13.3 1 11 12 1 0 db, 3 db
Tuner Section	
Tuning Frequency Range	
FM	87.5 MHz-107.9 MHz
AM	530 kHz-1,710 kHz
FM/AM Preset Memory	40 Stations
General	
Power Supply	AC 120 V~, 60 Hz
Power Consumption	4.3 A

No-Sound Power Consumption		
55 W		
Standby Power Consumption		
0.15 W		
Dimensions (W x H x D) 17 1/8" x 6 5/16" x 12 15/16"		
(435 × 160 × 328 mm)		

Weight

CARTON	
Dimensions (W x H x D)	21 1/8" × 10 7/16" × 16 3/8"
	(537 x 265 x 416 mm)
Weight	23.1 lbs. (10.5 kg)
UPC CODE	

17.2 lbs. (7.8 kg)

(B) 751398012198 Supplied Accessories

- Indoor FM antenna AM loop antenna
- Speaker setup microphone Instruction manual Remote controller AA (R6) batteries x 2



Due to a policy of continuous product improvement, Onkyo reserves the right to change specifications and appearance without notice. Manufactured under license from Dolby Laboratories. Dolby, Atmos, Pro Logic, and the double-D symbol are trademarks of Dolby Laboratories. For DTS patents, see http://patents.dts.com. Manufactured under license from DTS Licensing Limited, DTS, DTS-HD, the Symbol, & DTS and the Symbol together are registered trademarks, and DTS-HD Master Audio is a trademark of DTS, Inc. @ DTS, Inc. All Rights Reserved. HDMI, the HDMI logo, and hulling-Definition Multimedia Interface are trademarks or engistered trademarks of HDMI logos and the United States and other countries. The Bluetooth® word mark and logos are owned by the Bluetooth SIG, Inc. WRAT, Music Optimizer, CinemaFILTER, Theaten Dimensional, and AccuEQ are trademarks of Onlyo Corporation. All other trademarks and registered trademarks are the property of their respective holders.



04/15