

UHD60



Proyector para teatro en casa de ultra definición
4K



Features

- Resolución 4K UHD real de 3840×2160, con 3,000 brillantes lúmenes con colores cinemáticos
- Compatibilidad con HDR10 que produce blancos brillantes, negros profundos y colores realistas
- La tecnología HDMI 2.0 con HDCP 2.2 garantiza la compatibilidad con los últimos dispositivos 4K UHD para una gran calidad de imagen
- Desplazamiento de lente vertical y zoom 1.6x para una instalación fácil
- La tecnología UltraDetail permite hacer ajustes finos a la claridad de la imagen y brillo, resultando en una imagen con detalle mejorado

4K

2160P

HDCP 2.2

HDR
COMPATIBLE

HDMI™
HIGH DEFINITION MULTIMEDIA INTERFACE

NATIVE
16:9
WIDESCREEN

RoHS
compliant

Traiga la experiencia 4K a casa con el Optoma UHD60

El Optoma UHD60 es un proyector de ultra alta definición 4K con 3,000 lúmenes que entrega una calidad de imagen impresionante. Compatibilidad HDR10 con DCI-P3 de amplia gama de colores y tasa de contraste de 1,000,000:1 que produce increíbles colores cinematográficos con negros más profundos y blancos más brillantes.

Tienen en su interior el chip de Texas Instruments 4K UHD DLP, y cumple el estándar 4K HD de la CTA. El chip DLP de alto desempeño despliega 8.3 millones de píxeles simultáneos distintos en pantalla y proyecta imágenes de hasta 140 pulgadas.

La conectividad HDMI 2.0 con HDCP 2.2 garantiza la compatibilidad con fuentes de video 4K UHD. El desplazamiento de lente vertical de 15% y el zoom óptico de 1.6x ofrece flexibilidad en su instalación mientras que la lámpara de hasta 15,000 horas de vida garantiza la confiabilidad.

*Lamp life is dependent upon many factors, including lamp mode, display mode, usage, environmental conditions and more. Lamp brightness can decrease over time.

† 3D content can be viewed with DLP® Link active shutter glasses when projector is used with a compatible 3D player. Please visit Optoma.com for more information.

Optoma.com

Copyright © 2018 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments™. All other trademarks are the property of their respective owners. All specifications subject to change.

Published on 04/17/20

UHD60



ESPECIFICACIONES TÉCNICAS

Relación de aspecto	16:9
Audio	2x 4 Watt Stereo Speakers
Brillo	3,000 Lumens
Relación de Aspecto Compatible	16:9 (native), 4:3, Auto, LBX (2160p and 1080p)
Conexiones	1xHDMI 1.4a, 1xHDMI 2.0 (w/ HDCP 2.2, MHL 2.1 and Full 18Gbps), VGA-In, Audio-In (3.5mm), Audio-Out, SPDIF Out (Optical), USB 2.0 Port (Service), USB-A Power, RJ45, RS232C, 12V Trigger
Relación de contraste	Up to 1,000,000:1 with Dynamic Black
Tecnología de Pantalla	Single 0.66" TRP S610 4K UHD DMD DLP™ Technology by Texas Instruments
Colores visibles	1.07 Billion
Inputs	1xHDMI 1.4a, 1xHDMI 2.0 (w/ HDCP 2.2, MHL 2.1 and Full 18Gbps), VGA-In, Audio-In (3.5mm), USB 2.0 Port (Service), USB-A Power, RJ45, RS232C
Light Source Type	240W
Light Source Life	4,000/10,000/15,000 (Bright/ECO/Dynamic)
Lens Shift	Vertical: +15%
Maximum Resolution	4K (4096 x 2160) @ 60Hz with XPR Technology
Native Resolution	UHD (3840 x 2160)
Noise Level	25dB
Offset	100% (see Lens Shift)
On-Screen Display	"Complete on-screen menu, adjustments in 10 languages"
Operating Temperature	Sea Level to 10,000 feet (@73°F); must manually switch to high-altitude mode at 5,000 feet & above
Outputs	Audio out (3.5mm), SPDIF out (optical), 12V trigger
Power Supply	AC input 100-220V, 50-60Hz, auto-switching

Projection Distance	4.2' - 30.5'
Projection Lens	F/2.5~3.26; f=20.91~32.62mm
Projection Method	Front, rear, ceiling mount, tabletop
Projection Screen Size	26.45" - 302.2"
Remote Control	Full Function Home Remote Control

COMPATIBILITY SPECIFICATIONS

Computadora Compatible	4K UHD 2160p, WUXGA, HDTV 1080p, UXGA, SXGA, WXGA+, WXGA (1366x768), WXGA, HDTV (720p), XGA, SVGA, VGA, PC and Mac compatible
Conexiones	1xHDMI 1.4a, 1xHDMI 2.0 (w/ HDCP 2.2, MHL 2.1 and Full 18Gbps), VGA-In, Audio-In (3.5mm), Audio-Out, SPDIF Out (Optical), USB 2.0 Port (Service), USB-A Power, RJ45, RS232C, 12V Trigger
Velocidad de escaneo horizontal	31K~135KHz
Optional Wireless	Yes
RoHS	Compliant
Vertical Scan Rate	24 - 85Hz (120Hz for 3D)
Video Compatibility	480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(24/50/60Hz), 2160p(24/50/60Hz)

PHYSICAL SPECIFICATIONS

Dimensiones (W x H x D)	19.6" x 6" x 13"
Security	Security bar, Kensington lock, password protection, keypad lock
Weight	16 lbs

Other

Optional Accessories	HDCast Pro, ceiling mount,
Standard Accessories	Lens cap, AC power cord, HDMI cable, remote control, batteries for remote, multilingual CD-ROM, user's manual, quick start card, and warranty card
Warranty Info	2 Year Limited Warranty / 90 Days Lamp

*Lamp life is dependent upon many factors, including lamp mode, display mode, usage, environmental conditions and more. Lamp brightness can decrease over time.

† 3D content can be viewed with DLP® Link active shutter glasses when projector is used with a compatible 3D player. Please visit Optoma.com for more information.

Optoma.com

Copyright © 2018 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments™. All other trademarks are the property of their respective owners. All specifications subject to change.

Published on 04/17/20