Wide-Coverage All-Weather Loudspeaker



AW-500-SM

Easy to integrate into almost any outdoor environment, the AW-500-SM selectable mono/stereo wide-coverage model brings powerful and dynamic Klipsch sound to a wide variety of challenging installation locations.

Upholding the same high-performance standards as all our indoor products, the AW-500-SM employs a 5-inch IMG woofer and dual 1-inch titanium dome tweeters so that it can play both left and right stereo signals with total precision and clarity.

Perfect for small outdoor areas that cannot accommodate multiple speakers, the AW-500-SM can also bring smooth and even coverage to larger areas when multiple AW-500-SM's are used.

Other professional-grade features on the AW-500-SM include a switch that lets listeners easily select between mono and stereo configurations, durable UV-resistant enclosure, heavy gauge zinc C-bracket for added mounting strength and 3/8"-16 threaded inserts that fit popular third party mounts, making installation quick and simple.

Because it nicely blends in with its surroundings and offers installation flexibility, this amazing performer is sure to be a homeowner favorite.

- Very high sensitivity and power handling
- 3/8"-16 threaded insert for optional mounts
- Paintable UV-resistant ABS enclosure with rustproof aluminum grille
- Dual 90°x 90° Tractrix Horn tweeters for clean, clear highs
- Supplied with C-style mounting bracket and stainless steel hardware

SPECIFICATIONS

FREQUENCY RESPONSE	80Hz-20kHz \pm 3dB
SENSITIVITY	94dB @ 1 watt/1 meter
NOMINAL IMPEDANCE	8 ohms
CROSSOVER FREQUENCY	2700Hz
POWER HANDLING	75W (300 watts peak)
ENCLOSURE/MATERIAL TYPE	Sealed/ABS
DRIVE COMPONENTS	Two-way system using two 1" (2.54cm)
	polymer dome tweeters with two 90°x 90°
	Tractrix® Horns and one 5" (12.7cm)
	IMG woofer
WIRE GAUGE ACCOMMODATED	12
WEIGHT	10 lbs. (4.54kg)
HEIGHT	8" (20.32cm)
WIDTH	15.75" (40cm)
DEPTH	8.75" (22.23cm)
FINISH	White enclosure and grille
CROSSOVER FREQUENCY POWER HANDLING ENCLOSURE/MATERIAL TYPE DRIVE COMPONENTS WIRE GAUGE ACCOMMODATED WEIGHT HEIGHT WIDTH DEPTH	2700Hz 75W (300 watts peak) Sealed/ABS Two-way system using two 1" (2.54cm) polymer dome tweeters with two 90°x 90° Tractrix® Horns and one 5" (12.7cm) IMG woofer 12 10 lbs. (4.54kg) 8" (20.32cm) 15.75" (40cm) 8.75" (22.23cm)

