

MC-EW4051

Multi-purpose 3LCD Projector



Introducing our innovative multi-purpose 3LCD MC-EW4051 projector which combines all our technical expertise with our market leading knowledge.

This multi-purpose projector can produce 4000 ANSI, has a 20,000:1 contrast ratio and a resolution of 1280 x 800.

So whether you are on the move or in an office, our MC-EW4051 multi-purpose projector is the perfect solution for today's professionals. It combines portability and usability with powerful performance in a lightweight and compact design, enabling users to set it up and get working in seconds.

Key Features:

- WXGA 1280 x 800 resolution
- 4000 ANSI lumens / colour light output
- 20,000:1 contrast ratio
- Images up to 300" diagonal
- Built-In lens
- Filter life 10,000 hours
- 3 year/6 month warranty*



Please note: Content, technical specifications and images are subject to change.

**For education and extended warranties please contact your local dealer.*

MC-EW4051 3LCD Multi-purpose Projector

Technical Specifications

Display System	3 LCD 15mm (0.59")	On Screen Display Languages	English, French, German, Spanish, Italian, Norwegian, Dutch, Japanese, Portuguese, Simplified Chinese, Traditional Chinese, Korean, Swedish, Russian, Finnish, Polish, Turkey, Arabian, Persian, Czech, Danish, Hungarian, Romanian, Slovenian, Croatian, Greek, Lithuanian, Estonian, Latvian, Thai, Portuguese (Brazil), Indonesian, Vietnamese, Hebrew
Panel Structure	3LCD	Digital Input	HDMI x 2 (HDCP compliant)
Resolution	WXGA (1280 x 800)	Analogue Input	15-pin Mini-D-Sub x 1, RCA Jack x 1
Light Output (Brightness) ANSI Lumens (Normal)	4000 (Normal)	Video Output	15 pin Mini D-Sub x 1 (shared with analog computer input)
Contrast Ratio	20,000:1	Audio Input	3.5mm Stereo Mini Jack x 2, RCA Jack (L/R) x 1
Light Source	Lamp	Audio Output	3.5mm Stereo Mini Jack x 1
Lamp Life (hours)	6000 (Normal) / 12,500 (Eco)	RS-232C Control	1 x 9-pin D-Sub
Lens	Built-in	Wireless LAN	USB-WL-5GM wireless adapter (optional)
Number of colours	16.7 million colours	Wired LAN	RJ45 connector x 1
Lens Zoom	Manual zoom x 1.2	USB Type-A	USB Type A x 1 (PC less Presentation or Wireless adapter)
Lens Focus	Manual focus	USB Type B	USB Type B x 1 (USB display or USB mouse control)
Projection Lens F Number	1.6-1.8	Power Supply	AC 100V – 120V / AC 220V – 240V (50/60Hz)
Focus Distance	0.9 – 9.6m (Wide) / 1.1 – 11.6m (Tele)	Operating Power Consumption	310W
Distance to Width Ratio/ Throw Ratio (:1)	1.5 - 1.8	Standby Power Consumption	Less than 0.35W
Diagonal Display Size	30 - 300"	Weight	3.5kg
Installation	Ceiling, Tabletop, Rear	Dimensions (W x H x D)	349 x 264 x 88mm
Speakers	16W mono	Noise (Normal)	37dB (Normal) / 29dB (Whisper)
Digital Keystone Correction (Degrees)	Horizontal ± 30°, Vertical ± 30°	Filter Life (Hours)	10,000
Picture Modes	Normal, Cinema, Dynamic, Board (Black), Board (Green), Whiteboard, Daytime, Photo, DICOM SIM	Certification	CE Marking, EN61000-3-2, EN61000-3-3, EN55032 (class B), EN55035 (EMC directive), EN60950-1 (Low voltage directive), WEEE/RoHS/ErP compliant
Picture Adjustments	ASPECT selection (Normal/4:3/16:9/16:10/14:9/Zoom), Perfect Fit (4 corners and 4 sides), Frame Lock (Data signal with vertical frequency of 49 to 51 Hz, 59 to 61 Hz), HDCR, Image blank by RS232C/Remote control, Image Optimizer, Magnify, Mirror Reverse Image, Up-side Down Image	Computer	IBM Compatible VGA, SVGA, XGA, WXGA, WXGA+/SXGA/SXGA+/WSXGA+/UXGA/HD (Compressed), MAC16"
Operating Features	Audio pass through, Audio ports assign, Audio out (standby) and monitor out / selectable source with MENU, Auto eco mode, Auto power off, Auto signal search, Direct power on, Image blank by RS232C/Remote control, LED lamps (power, lamp, temp), Magnify 4 times (XGA) by RS232C / remote control, MyButton by remote control, MyMemory, MySource, MyText, MyScreen, Picture freeze by RS-232C / remote control, Serial number displayed on EASY MENU and on the side of projector, Source naming (in English), Stand-by audio	Video	525i (480i), 525p (480p), 625i (576i), 1125i (1080i@50/60), 750p (720p@50/60), 1125p (1080p@50/60)
Network Features	AMX Device Discovery, Command Control via the Network, Configuring and Controlling the Projector via a Web Browser, Controlling the Projector via Scheduling, Crestron RoomView® (Not accessible through the wireless adapter), Displaying text data transferred via network, Failure and Warning Alerts via E-mail, My Image (still image transfer) Display, Network Bridge, Network Presentation (PC still picture transfer), Frame rate (practical) is under 12fps (640x480 movie)	Supplied Accessories	Power Cable (1.8m) x1, Computer Cable (2m) x1, IR Remote Control Unit x1, AA Batteries x2, Concise User Manual x1, Security Label x1, Lens Cover x1, Adapter Cover x1
Security Features	PIN Security Lock, MyScreen Password Lock, Transition Detector, MyText Password Lock, Key Lock (Key pad, Remote Control)	Optional Accessories	USB wireless adapter USB-WL-5GM
		Remote Control	HL03037
		Replacement Lamp, Filter	DT02081M (without Filter), UX39561
		Projector/Lamp Warranty	3 years / 6 months (for education and extended warranties please contact your local dealer)



maxell
Within, the Future

Maxell Limited
Whitebrook Park
Lower Cookham Road, Maidenhead
Berkshire, SL68YA
Tel: +44 (0)1628 585 000
Fax: +44 (0)1628 585 163
www.maxelldisplay.com

Specification and photography subject to change.