

AIR® 6.5" Landscape Speakers

- > Weatherproof 2-way outdoor speakers
- > Designed for landscape and wall mount applications
- > High-performance 6.5" coaxial drivers
- > 8 Ohms nominal impedance
- > Built-in 70/100 Volt transformer
- > 75 Watts program power handling at 8 Ohms
- > 80Hz-20kHz frequency range
- > 105° nominal coverage pattern
- > Attractive bronze textured finish
- > Metal ground stake with security plate
- > Surface mount wall bracket
- > Adjustable positioning
- > Sold in pairs

AIR® Landscape Speakers by Crestron® deliver high-performance audio to all corners of your property. These unimposing weatherproof speakers blend in wherever you put them while providing sound quality rivaling any great indoor speaker.

The AIR LS6T model provides a pair of weatherproof 2-way speakers designed to be mounted to the surface of an exterior wall or fence post, or staked directly into the ground. Each speaker features a 6.5 inch woofer with a coaxially mounted 0.8 inch dome tweeter. Power handling is 75 Watts (program) at 8 Ohms, with a usable frequency range from 80 Hz to 20 kHz (-10 dB). A built-in transformer allows for use with 70 and 100 Volt distributed speaker systems.

AIR landscape speakers come complete with the choice of surface mount wall brackets and ground stakes included.

- **Surface Mount Wall Brackets** — The wall brackets achieve a clean, streamlined appearance while affording a secure and stable installation on any flat, vertical surface. Pitch and yaw adjustments allow the speakers to be positioned both vertically and horizontally to direct sound toward the intended listening area and away from the neighbors.
- **Ground Stakes** — The ground stakes allow for installation amongst plants and landscaping in a typical soil or rock bed. Each ground stake features durable metal construction and includes an underground security plate to deter theft and hold the speakers firmly in place.

Each speaker can be operated at 8 Ohms, 70 Volts, or 100 Volts. Also known as "constant-voltage", 70 Volt and 100 Volt speaker systems allow for long wire runs using small-gauge wire, and provide the potential for connecting numerous speakers per circuit as is common with outdoor speakers. Setting the 70/100V transformer tap is performed via a screwdriver-adjustable control located on the rear of each speaker.

Each AIR LS6T includes a short length of direct-burial wire that is permanently attached to the speaker and routed through the mounting base for a clean, reliable installation. A suitable electrical box (not included) is advised for termination of the speaker wiring. A pair of waterproof wire nuts is included.



AIR landscape speakers feature an attractive dark bronze textured finish, and can be painted to blend with surrounding landscape or architecture. They are priced and sold in pairs.

SPECIFICATIONS

Features & Performance

- Woofer:** 6.5 inch (165 mm) polypropylene w/rubber surround & steel basket
- Tweeter:** 0.8 inch (20 mm) treated cloth dome, coaxially mounted
- Crossover Frequency:** 2.5 kHz
- Impedance:** 8 Ohms nominal with transformer set to "8Ω"
- Transformer Taps:** 3.75W or 15W at 70V;
7.5W at 100V
- Frequency Response:** 100 Hz to 20 kHz (±3 dB)
- Frequency Range:** 80 Hz to 20 kHz (-10 dB)
- Power Handling:** 75 Watts program (8 Ohms)
- Sensitivity:** 85 dB @ 1W/1m
- Coverage:** 105° conical (nominal)

AIR LS6T AIR® 6.5” Landscape Speakers

Connections

Input: (1) 3 feet (1 m) attached direct burial cable containing (2) 16 AWG (1.31 mm²) conductors, unterminated; includes two waterproof wire nuts; requires a suitable electrical junction box (not included)

Controls

Transformer Tap: (1) Recessed screwdriver-adjustable rotary switch on rear; used to select 70/100V tap or 8 Ohms (bypass)

Environmental

Temperature: -2° to 120°F (-19° to 49°C)

Humidity: 5% to 100% RH (non-condensing)

Splash Resistance: IPx4 rated per IEC 60529

Construction

Enclosure: Glass fiber reinforced ABS plastic, bronze textured finish, paintable, security tether tie point

Grille: Metal, black powder coat painted

Surface Mounting: Includes surface mount wall brackets for attachment to a solid flat vertical surface; allows adjustment of yaw (horizontal angle) and pitch (vertical angle)

Ground Stake Mounting: Includes 17 inch (43 cm) metal ground stake and 6.6 inch (168 mm) diameter underground security plate; allows adjustment of pitch (vertical angle)

Dimensions

Height: 26.09 in (663 mm) with ground stake;
10.42 in (265 mm) with wall bracket

Width: 6.99 in (178 mm)

Depth: 11.11 in (283 mm) with ground stake;
11.99 in (305 mm) with wall bracket

NOTE: All dimensions omit the underground security plate

Weight

4.25 lb (1.90 kg) per speaker

MODELS & ACCESSORIES

Available Models

AIR LS6T-BRZ-T: AIR® 6.5” Landscape Speakers, Bronze Textured, Pair

Available Accessories

AIR IGS82T: AIR® Dual 8” In-Ground Subwoofer

Notes:

Crestron warrants to the original end purchaser that this Crestron Speaker Product, when purchased directly from Crestron or an authorized Crestron Dealer, will be free from defects in material and workmanship for the life of the product except for speaker grills and outdoor rated speakers, which are warranted for five (5) years. Crestron will at its option and expense either repair the defect or replace the Speaker Product with a new or remanufactured Product or a reasonable equivalent. In cases where a new model is substituted, a modification to the mounting surface may be required. If mounting surface modification is required, Crestron assumes no responsibility or liability for such modifications.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at www.crestron.com/salesreps or by calling 800-237-2041.

The specific patents that cover Crestron products are listed online at: patents.crestron.com.

Crestron, the Crestron logo, and AIR are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2015 Crestron Electronics, Inc.

AIR LS6T AIR® 6.5" Landscape Speakers

