

ASPIRE IC8-W-T

Aspire® 8" 2-Way In-Ceiling Speakers, White Textured

- > Audiophile performance 2-way in-ceiling speakers
- > 8" (203 mm) woven poly-glass composite woofers
- > 1" (25 mm) advanced synthetic polymer dome tweeters
- > 4th order crossovers
- > Steel composition woofer baskets
- > Vented pole pieces
- > "Zero-bezel" frameless steel grilles, paintable
- > Three-point, spring-loaded swiveling dog mounting system
- > 150 Watts program power handling
- > 48Hz – 20kHz frequency response
- > 8 Ohms nominal impedance
- > Sold in pairs

The product of expert Crestron® audio engineering, Aspire® speakers deliver high-end performance for demanding residential installations. Select materials and a refined appearance underscore the meticulous design behind each model. The result is a complete line of in-wall and in-ceiling speakers worthy of a place in every room of the finest custom home.

The Aspire line strikes a perfect balance between performance and price, delivering pristine, impactful sound quality, with minimal impact on your decor thanks to paintable zero-bezel grilles. Streamlined installation of each speaker is facilitated through a three-point, spring-loaded swiveling dog mounting system optimized to minimize interference with obstructions within the ceiling space.

The Aspire IC8-W-T model provides a pair of 2-way in-ceiling speakers featuring 8 inch (203 mm) woven poly-glass composite woofers for rich, impactful low end, and 1 inch (25 mm) advanced synthetic polymer dome tweeters for crisp, soaring highs. Offset post-mounting of the tweeters reduces midrange frequency response anomalies normally caused by interference between the woofer and the back of the tweeter. Precisely tuned 4th order crossovers ensure a full, warm and detailed response across the spectrum. Power handling is an impressive 150 Watts (program), with a wide frequency response from 48 Hz to 20 kHz (± 3 dB).

SPECIFICATIONS

Features & Performance

Woofer: 8 inch (203 mm) woven poly-glass composite w/rubber surround, vented pole piece & steel basket

Tweeter: 0.98 inch (25 mm) advanced synthetic polymer dome, ferrofluid cooling, offset post-mounted

Crossover: 4th order

Crossover Frequency: 2.5 kHz

Impedance: 8 Ohms nominal



Frequency Response: 48 Hz to 20 kHz (± 3 dB)

Frequency Range: 40 Hz to 20 kHz (-10 dB)

Power Handling: 150 Watts program

Sensitivity: 89.5 dB @ 1W/1m

Connections

Input: (2) Spring terminals;

Maximum Wire Size: 10 AWG (6 mm²)

Environmental

Temperature: 41° to 104° F (5° to 40° C)

Humidity: 10% to 90% RH (non-condensing)

For indoor use only

Construction

Baffle: ABS plastic, black

Grille: Steel with white textured finish, paintable, magnetically-held "zero-bezel" frameless design

Mounting: Flush ceiling mount using 3 integral spring-loaded swiveling dogs, 1.35 in (34 mm) maximum surface thickness, 4.47 in (114 mm) minimum mounting depth, 10.80 in (275 mm) diameter recommended cutout

Dimensions

Diameter: 11.64 in (296 mm) not including mounting dogs

Depth: 4.66 in (119 mm)

Dimensions shown are per speaker

Weight

6.05 lb (2.75 kg) per speaker

ASPIRE IC8-W-T Aspire® 8" 2-Way In-Ceiling Speakers

MODELS & ACCESSORIES

Available Models

ASPIRE IC8-W-T: Aspire® 8" 2-Way In-Ceiling Speakers, White Textured, Pair

Available Accessories

SPKA-NCTP-IC800: New-Construction Speaker Templates, 1 Pair

SPKA-GRILLE-IC802: Round Grilles, White, 10 Pack (for replacement)

ASPIRE IWS82-W-T-EACH: Aspire® In-Wall Dual 8" Subwoofer, White Textured, Single

Notes:

Crestron warrants to the original end purchaser that this Crestron Speaker Product, when purchased directly from Crestron or an authorized Crestron Dealer, will be free from defects in material and workmanship for the life of the product except for speaker grilles and outdoor rated speakers, which are warranted for five (5) years. Crestron will at its option and expense either repair the defect or replace the Speaker Product with a new or remanufactured Product or a reasonable equivalent. In cases where a new model is substituted, a modification to the mounting surface may be required. If mounting surface modification is required, Crestron assumes no responsibility or liability for such modifications.

This product may be purchased from an authorized Crestron dealer. To find a dealer, please contact the Crestron sales representative for your area. A list of sales representatives is available online at <https://www.crestron.com/How-To-Buy/Find-a-Representative> or by calling 855-263-8754.

The specific patents that cover this and other Crestron products are listed online at <https://www.crestron.com/legal/patents>.

Certain Crestron products contain open source software. For specific information, visit <https://www.crestron.com/opensource>.

Crestron, the Crestron logo, Aspire, Essence, and Excite are either trademarks or registered trademarks of Crestron Electronics, Inc. in the United States and/or other countries. Other trademarks, registered trademarks, and trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Crestron disclaims any proprietary interest in the marks and names of others. Crestron is not responsible for errors in typography or photography. Specifications are subject to change without notice. ©2018 Crestron Electronics, Inc.

